


1. Install the ice maker properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.
3. Product code: M028, G008, S-21873



ITEM	Hoshizaki Cube Ice Maker	
MODEL	IM-220AA-B-801SA	
AC SUPPLY VOLTAGE	1 PHASE 220-240V 50Hz	
AMPERAGE	5.0A (AT.32°C, WT.21°C)×2	
STARTING AMPERAGE	24A×2	
ELECTRIC CONSUMPTION	950W (AT.32°C, WT.21°C)×2	
POWER FACTOR	82%	
POWER SUPPLY CAPACITY	Min. 1.51KVA (6.6A)×2	
ICE PRODUCTION PER 24h	Approx. 190(5mm)/220(15mm)kg (AT.10°C, WT.10°C)×2 Approx. 180(5mm)/200(15mm)kg (AT.21°C, WT.15°C)×2 Approx. 160(5mm)/175(15mm)kg (AT.32°C, WT.21°C)×2	
WATER CONSUMPTION PER 24h	Approx. 0.62m³(AT.10°C, WT.10°C)×2 Approx. 0.31m³(AT.21°C, WT.15°C)×2 Approx. 0.27m³(AT.32°C, WT.21°C)×2	
SHAPE OF ICE	Cube Approx. 28×28×23mm	
FREEZE CYCLE TIME	Approx. 23min (AT.21°C, WT.15°C)	
ICE PRODUCTION PER CYCLE	Approx. 3.2kg/140.pcs×2 (AT.21°C, WT.15°C)	
MAX STORAGE CAPACITY	Approx. 286kg Maximum 348kg	
DIMENSIONS	1219mm(W)×820mm(D)×1886mm(H)	
EXTERIOR	Stainless Steel	
BIN	EXTERIOR Stainless Steel, Galvanized Steel(Rear) INTERIOR Polyethylene	
INSULATION FOAM BLOWING AGENT	Cyclopentane/CFC Free/ODP: 0/GWP: 3	
CONNECTIONS-ELECTRIC	X-Type Connection	
CONNECTIONS-WATER SUPPLY	Inlet G3/4 (connected at rear side)	
CONNECTIONS-DRAIN	Outlet R3/4 (connected at rear side)	
ICE MAKING SYSTEM	Cell type	
HARVESTING SYSTEM	Hot Gas Defrost	
COMPRESSOR	Hermetic	
CONDENSER	Air-cooled, Fin and Tube type	
HEAT REJECTION	2290W(1970kcal/h) (AT.32°C, WT.21°C)×2	
EVAPORATOR	Tin-plated Copper Tube on Sheet and Cells	
REFRIGERANT CONTROL	Thermostatic Expansion Valve	
REFRIGERANT CHARGE	R404A/500g	
ICE MAKING CONTROL SYSTEM	Thermistor, Timer	
HARVESTING CONTROL SYSTEM	Thermistor	
BIN CONTROL SYSTEM	Microswitch with Time Delay	
ICE MAKING WATER CONTROL SYSTEM	Timer, Water Pan's movement	
ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse	
COMPRESSOR PROTECTION	Auto-reset Overload Protector	
ICE MAKER PROTECTION	Interlock by Controller Board	
WEIGHT	ICE MAKER: Net weight 69kg×2/Gross weight 76kg×2 BIN: Net weight 64kg/Gross weight 86kg	
ACCESSORIES	Scoop, Leg(4 pcs), Installation Kit	
OPERATING CONDITIONS	Ambient Temp.: 1 - 40°C, Water Supply Temp.: 5-35°C Water Supply Pressure: 0.7-7.8bar(0.07-0.78MPa), Voltage Range: Rated Voltage±6%	

■ We reserve the right to make changes in specifications and design without prior notice.

HOSHIZAKI CUBE ICE MAKER IM-220AA-B-801SA

APPROVED YOSHIDA	CHECKED YOSHIDA	DESIGNED KONDO	DRAWN WATANABE	SCALE 1/20	TRIGONOMETRY
KUROYANAGI APPROVED	UEDA DESIGNED	2013.06.06 DATE	DATE 2013.03.11	DRAWING NO. D12692	SYMBOL ▲