



1. Install the sushi case properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. Relative humidity exceeding 60% may result in excessive condensation on the exterior.
3. The food temperature is controllable by turning over the food mounts.
4. Product Code: S051-C169

	ITEM	Hoshizaki Counter Showcase	
	MODEL	HNC-120BC-L-B	
△	POWER SUPPLY	1 Phase 220V 50Hz Capacity: 0.24kVA (1.10A)	
△	AMPERAGE	Running: 0.8A Rated: 0.8A Starting: 4A	
△	ELECTRIC CONSUMPTION	Rated Motor: 90W (Power Factor: 51%)	
△	HEAT REJECTION	185W	
	PULL DOWN TIME (10° C)	Approx. 30min. (Ambient Temp. 30° C, No Load)	Measured 20 mm above the food mount (normal position) located at the interior bottom center
	SATURATION TEMPERATURE	Approx. 5° C (Ambient Temp. 30° C, No Load)	
	POWER CORD	2.4m	
△	EFFECTIVE CAPACITY	42L/30L (according to Chinese energy efficiency regulation)	
	OUTSIDE DIMENSIONS	1200mm (W) x 345mm (D) x 270mm (H)	
	INSIDE DIMENSIONS	845mm (W) x 288mm (D)[Floor] x 157mm (H)	
	EXTERIOR	Clear Glass, ABS Plastic, PVC Plastic	
	INTERIOR	Clear Glass, ABS Plastic, Stainless Steel	
	INSULATION	Polyurethane Foam	
	INSULATION FOAM BLOWING AGENT	HFO-1233zd(E)	
	DOOR	Sliding Glass x 2[435mm (W) x 172mm (H)]	
	REFRIGERATION SYSTEM	Convection Cooling	
	DEFROST SYSTEM	N/A	
△	COMPRESSOR	Hermetic 75W	
	CONDENSER	Fin and Tube type, Cooling Fan Motor provided	
	EVAPORATOR	(Upper) Tube Type, (Lower) Pipe on Sheet Type	
△	REFRIGERANT	R134a/150g	
	ELECTRICAL CIRCUIT PROTECTION	Earth Leakage Circuit Breaker (with Overcurrent Protector)15A Earth Wire	
	COMPRESSOR PROTECTION	Motor Protector	
	WEIGHT	32kg (Gross 43kg)	
	PACKAGE	Carton (Wooden Pallet) 1280mm (W) x 415mm (D) x 465mm (H)	
	ACCESSORIES	Food Mount x 3, Joint, Drain Hose	
	OPERATING CONDITIONS	Ambient Temperature:10 - 30° C Voltage Range:Rated Voltage ±6%	

\*We reserve the right to make changes in specifications and design without prior notice.

