HOSHIZAKI

Measured 20 mm above the food

mount (normal position) located

at the interior bottom center

Hoshizaki Counter Showcase

1 Phase 220V 50Hz Capacity: 0.37kVA (1.55A)

Running: 1.0A Rated: 1.0A Starting: 6A

Rated Motor: 150W (Power Factor: 52%)

DRAWING NO.

D06644

HNC-180BC-L-B

(Ambient Temp. 30° C, No Load

(Ambient Temp. 30° C, No Load

370W

Approx. 30min.

Approx. 5° C

1. Install the sushi case properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).

ITEM

MODEL

ELECTRIC

POWER SUPPLY

AMPERAGE

CONSUMPTION

HEAT REJECTION

PULL DOWN

TIME (10° C)

SATURATION

INOUE YORITA

APPROVED DESIGNED SYMBOL

ß

2019.04.16

2010.05.07

TEMPERATURE

- 2. Relative humidity exceeding 60% may result in excessive condensation on the exterior.
- 3. The food temperature is controllable by turning over the food mounts.
- 4. Product Code: S055-C169

